





SPACESAVER™ SYSTEMS

AVR75 INTERLOCK™ MODULE


24/48 VOLT SYSTEM DIMENSIONS



No. Cells/Module	No. Plates/Cell	System Volts	No. Stacks	No. of Modules High	Total No. of Modules	Capacity C/8 @ 1.75 vpc	Dimensions			
							Length (mm)	Depth ¹ (mm)	Height ² (mm)	Weight ³ (kgs.)
6	5	24	1	2	2	160	14.55" (370)	25.25" (641)	21.58" (548)	521 lbs. (236)
	5	48	1	4	4	160	14.55" (370)		37.66" (957)	993 lbs. (450)
	7	24	1	2	2	235	19.00" (483)		21.58" (548)	682 lbs. (309)
	7	48	1	4	4	235	19.00" (483)		37.66" (957)	1310 lbs. (594)
	9	24	1	2	2	310	23.50" (597)		21.58" (548)	842 lbs. (382)
	9	48	1	4	4	310	23.50" (597)		37.66" (957)	1626 lbs. (738)
	11	24	1	2	2	390	28.00" (711)		21.58" (548)	1004 lbs. (455)
	11	48	1	4	4	390	28.00" (711)		37.66" (957)	1946 lbs. (883)
	13	24	1	2	2	470	32.50" (826)		21.58" (548)	1165 lbs. (528)
	13	48	1	4	4	470	32.50" (826)		37.66" (957)	2263 lbs. (1026)
	15	24	1	2	2	550	37.00" (940)		21.58" (548)	1326 lbs. (601)
	15	48	1	4	4	550	37.00" (940)		37.66" (957)	2580 lbs. (1170)
4	5	24	1	3	3	160	9.70" (246)	25.25" (641)	29.62" (752)	515 lbs. (234)
	5	48	1	6	6	160	9.70" (246)		53.74" (1365)	986 lbs. (447)
	7	24	1	3	3	235	12.66" (322)		29.62" (752)	674 lbs. (306)
	7	48	1	6	6	235	12.66" (322)		53.74" (1365)	1301 lbs. (590)
	9	24	1	3	3	310	15.66" (398)		29.62" (752)	833 lbs. (378)
	9	48	1	6	6	310	15.66" (398)		53.74" (1365)	1616 lbs. (733)
	11	24	1	3	3	390	18.66" (474)		29.62" (752)	992 lbs. (450)
	11	48	1	6	6	390	18.66" (474)		53.74" (1365)	1931 lbs. (876)
	13	24	1	3	3	470	21.66" (550)		29.62" (752)	1150 lbs. (522)
	13	48	1	6	6	470	21.66" (550)		53.74" (1365)	2245 lbs. (1018)
	15	24	1	3	3	550	24.66" (626)		29.62" (752)	1309 lbs. (594)
	15	48	1	6	6	550	24.66" (626)		53.74" (1365)	2560 lbs. (1161)



6 Cell (5–15 plates)



4 Cell (5–15 plates)

- ¹ Includes module and front shield.
- ² Height includes 4" base support. For overall height dimension (top termination) add top bracket (1.5") and terminal shield (6.25").
- ³ Weight includes cells, module and base support, but not the cell hardware.




SPACESAVER™ SYSTEMS


AVR75 INTERLOCK™ MODULE

24/48 VOLT SYSTEM DIMENSIONS (cont.)

No. Cells/Module	No. Plates/Cell	System Volts	No. Stacks	No. of Modules High	Total No. of Modules	Capacity C/8 @ 1.75 vpc	Dimensions			
							Length (mm)	Depth ¹ (mm)	Height ² (mm)	Weight ³ (kgs.)
3	17	24	1	4	4	630	21.90" (556)	25.25" (641)	37.66" (957)	1536 lbs. (697)
	17	48	1	8	8	630	21.90" (556)		69.82" (1773)	3016 lbs. (1368)
	19	24	1	4	4	705	24.15" (613)		37.66" (957)	1695 lbs. (769)
	19	48	1	8	8	705	24.15" (613)		69.82" (1773)	3331 lbs. (1511)
	21	24	1	4	4	785	26.40" (671)		37.66" (957)	1853 lbs. (841)
	21	48	1	8	8	785	26.40" (671)		69.82" (1773)	3645 lbs. (1653)
	23	24	1	4	4	865	28.65" (728)		37.66" (957)	2011 lbs. (912)
	23	48	1	8	8	865	28.65" (728)		69.82" (1773)	3959 lbs. (1796)
	25	24	1	4	4	945	30.90" (785)		37.66" (957)	2157 lbs. (978)
	25	48	1	8	8	945	30.90" (785)		69.82" (1773)	4249 lbs. (1927)
	27	24	1	4	4	1025	33.15" (842)		37.66" (957)	2319 lbs. (1052)
	27	48	1	8	8	1025	33.15" (842)		69.82" (1773)	4571 lbs. (2073)
	29	24	1	4	4	1100	35.40" (899)		37.66" (957)	2477 lbs. (1124)
	29	48	1	8	8	1100	35.40" (899)		69.82" (1773)	4885 lbs. (2216)
	31	24	1	4	4	1175	37.65" (956)		37.66" (957)	2635 lbs. (1195)
	31	48	1	8	8	1175	37.65" (956)		69.82" (1773)	5199 lbs. (2358)
33	24	1	4	4	1255	39.90" (1013)	37.66" (957)	2795 lbs. (1268)		
33	48	1	8	8	1255	39.90" (1013)	69.82" (1773)	5515 lbs. (2502)		
2	17	24	1	6	6	630	14.60" (371)	25.25" (641)	53.74" (1365)	1525 lbs. (692)
	17	48	2	6	12	630	29.20" (742)		53.74" (1365)	3050 lbs. (1383)
	19	24	1	6	6	705	16.10" (409)		53.74" (1365)	1683 lbs. (763)
	19	48	2	6	12	705	32.20" (818)		53.74" (1365)	3366 lbs. (1527)
	21	24	1	6	6	785	17.60" (447)		53.74" (1365)	1840 lbs. (835)
	21	48	2	6	12	785	35.20" (894)		53.74" (1365)	3680 lbs. (1669)
	23	24	1	6	6	865	19.10" (485)		53.74" (1365)	1998 lbs. (906)
	23	48	2	6	12	865	38.20" (970)		53.74" (1365)	3996 lbs. (1813)
	25	24	1	6	6	945	20.60" (523)		53.74" (1365)	2143 lbs. (972)
	25	48	2	6	12	945	41.20" (1046)		53.74" (1365)	4286 lbs. (1944)
	27	24	1	6	6	1025	22.10" (561)		53.74" (1365)	2300 lbs. (1043)
	27	48	2	6	12	1025	44.20" (1123)		53.74" (1365)	4600 lbs. (2087)
	29	24	1	6	6	1100	23.60" (599)		53.74" (1365)	2458 lbs. (1115)
	29	48	2	6	12	1100	47.20" (1199)		53.74" (1365)	4916 lbs. (2230)
	31	24	1	6	6	1175	25.10" (638)		53.74" (1365)	2621 lbs. (1189)
	31	48	2	6	12	1175	50.20" (1275)		53.74" (1365)	5242 lbs. (2378)
33	24	1	6	6	1255	26.60" (676)	53.74" (1365)	2779 lbs. (1261)		
33	48	2	6	12	1255	53.20" (1351)	53.74" (1365)	5558 lbs. (2521)		



3 Cell (17–33 plates)



2 Cell (17–33 plates)

¹ Includes module and front shield.

² Height includes 4" base support. For overall height dimension (top termination) add top bracket (1.5") and terminal shield (6.25").

³ Weight includes cells, module and base support, but not the cell hardware.

"POWERED FOR PERFORMANCE"™

DISTRIBUTED BY:

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4781

Order Department Hotline: 610-682-3262

www.eastpennunigy.com • e-mail: sales@eastpennunigy.com

E.P.M. Form No. 1147 6/04

© 2004 by EPM Printed in U.S.A.

All data subject to change without notice. No part of this document may be copied or reproduced, electronically or mechanically, without written permission from the company.